

Non-collapsible Fire and Utility Hose - Red

Features:

- outer construction is designed to withstand abrasion
- working pressure: **200 PSI** at ambient temperature (70°F)
- burst pressure: **600PSI** at ambient temperature (70°F)
- consult Dixon™ for pricing and availability of other lengths, threads and configurations
- also available with chrome brass fittings

Coupled with female and male NST (NH) thread, rocker lug, brass expansion ring couplings

Size	Length	Part #	List Price
1½"	50'	15B15-50RBF	\$1173.10
1½"	75'	15B15-75RBF	1632.30
1½"	100'	15B15-100RBF	1953.70



Coupled with female and male NPSH thread, rocker lug, brass expansion ring couplings

Size	Length	Part #	List Price
1½"	50'	15B15-50RBS	\$1173.10
1½"	75'	15B15-75RBS	1632.30
1½"	100'	15B15-100RBS	1953.70



Coupled with female and male NST (NH) thread, rocker lug, aluminum expansion ring couplings

Size	Length	Part #	List Price
1½"	50'	15B15-50RAF	\$864.85
1½"	75'	15B15-75RAF	1106.00
1½"	100'	15B15-100RAF	1450.00



Coupled with female and male NPSH thread, rocker lug, aluminum expansion ring couplings

Size	Length	Part #	List Price
1½"	50'	15B15-50RAS	\$864.85
1½"	75'	15B15-75RAS	1106.00
1½"	100'	15B15-100RAS	1450.00

P

Brass Female to Male Hex Nipples

Feature:

- required to switch hose from NPT to NST, or NST to NPT for continuous flow reels



Female Thread	Male Thread	Cast Brass Part #	Price
1½" NPT	1½" NST (NH)	FM1515F	\$20.60
1½" NST (NH)	1½" NPT	FM15F15T	18.40

- All adapters are made to approved Dixon™ specifications.