

Dixon™ Large Diameter (LDH) Gate Valves

Application:

- used on the suction intake and discharge sides of a pumper or on a hydrant

Features:

- 30° elbow needs only 8 easy turns to open and close
- non-rising stem, with an air bleed off
- finish anodized throughout - minimum thickness 0.001"
- maximum operating pressure: **280 PSI** at 70°F (21°C), without relief valve
- 4½" minimum waterway

Storz x Storz

Inlet Storz	Outlet Storz	Alum. Alloy, 356-T6 Part #	Price	Length	Width	Height
4"	4"	SGV440	\$2190.80	9"	6¼"	19½"
4"	5"	SGV450	2468.20	9"	7¾"	19½"
5"	4"	SGV540	2503.35	9"	7¾"	19½"
5"	5"	SGV550	2375.65	9"	7¾"	19½"

- all measurements include handles



Storz x Storz 30° with PRV

Inlet Storz	Outlet Storz	Alum. Alloy, 356-T6 Part #	Price	Length	Width	Height
4"	4"	SGV30-440	\$2253.10	9"	6¼"	20.0"
4"	5"	SGV30-450	2572.55	9"	7¾"	20.0"
5"	4"	SGV30-540	2607.70	9"	7¾"	20.0"
5"	5"	SGV30-550	2705.90	9"	7¾"	20.0"

- all measurements include handles



Storz x Female Swivel

Inlet Storz	Outlet Female NST Swivel	Alum. Alloy, 356-T6 Part #	Price	Length	Width	Height
4"	4"	FSGV440F	\$2217.55	9"	6"	19½"
4"	4½"	FSGV445F	2222.40	9"	6½"	19½"
4"	5"	FSGV450F	2344.40	9"	7"	19½"
4"	6"	FSGV460F	2350.80	9"	8"	19½"
5"	4"	FSGV540F	2342.95	9"	6"	19½"
5"	4½"	FSGV545F	2347.75	9"	6½"	19½"
5"	5"	FSGV550F	2469.75	9"	7"	19½"
5"	6"	FSGV560F	2392.90	9"	8"	19½"

- all measurements include handles



P