

# Global Forged Angle Hose Valves



**Features:**

- to be used with a fire hose rack assembly, or as a fire department outlet connection
- U/L listed and FM approved
- red steel handwheel
- maximum operating pressure: **300 PSI** at 70°F (21°C)
- polished or chrome plated parts with other outlet threads are also available, consult Dixon™ for information

**Female x Male**

| Inlet Female NPT | Outlet Male Thread | Forged Brass Part # | Price/E         |
|------------------|--------------------|---------------------|-----------------|
| 1½"              | 1½" NST (NH)       | <b>AV151</b>        | <b>\$174.05</b> |
| 2½"              | 2½" NST (NH)       | <b>AV251</b>        | <b>302.75</b>   |
|                  | 2½" NYC            | <b>AV251NYC</b>     | <b>302.75</b>   |
|                  | 2½" NYFD           | <b>AV251NYFD</b>    | <b>302.75</b>   |
|                  | 3" NST             | <b>AV2531</b>       | <b>414.00</b>   |



**Female x Female**

| Inlet Female NPT | Outlet Female NPT | Forged Brass Part # | Price/E         |
|------------------|-------------------|---------------------|-----------------|
| 1½"              | 1½"               | <b>AVF151</b>       | <b>\$174.05</b> |
| 2½"              | 2½"               | <b>AVF251</b>       | <b>302.75</b>   |

**Replacement Parts**

| Description                     | Part #           | Price/E        |
|---------------------------------|------------------|----------------|
| handwheel for 1½" valve         | <b>AV151-WR</b>  | <b>\$32.90</b> |
| handwheel for 2½" valve         | <b>AV251-WR</b>  | <b>36.35</b>   |
| handwheel nut for 1½" valve     | <b>AV151-N</b>   | <b>1.40</b>    |
| handwheel nut for 2½" valve     | <b>AV251-N</b>   | <b>1.35</b>    |
| valve seal rubber for 1½" valve | <b>AV151-RBR</b> | <b>16.95</b>   |
| valve seal rubber for 2½" valve | <b>AV251-RBR</b> | <b>15.15</b>   |



# 500# Angle Hose Valves



**Applications:**

- Typical applications are in fire department, gravity and pressure tank connections, test connections, and public water supplies to sprinkler and standpipe systems; designed and approved to manage 500 PSI pressures in piping systems where it is necessary to access the system for a fire hose connection.

**Features:**

- red handwheel
- FM approved
- New York City Board of Standards and Appeals, approval # MEA 54-07-E
- maximum operating pressure: **500 PSI** at 70°F (21°C)

| Inlet Female NPT | Outlet Male Thread | Cast Brass Part #  | Price/E         |
|------------------|--------------------|--------------------|-----------------|
| 2½"              | 2½" NST (NH)       | <b>AV5-250F</b>    | <b>\$711.25</b> |
| 2½"              | 2½" NYFD           | <b>AV5-250NYFD</b> | <b>711.25</b>   |

| Inlet Female NPT | Outlet Female NPT | Cast Brass Part # | Price/E         |
|------------------|-------------------|-------------------|-----------------|
| 2½"              | 2½"               | <b>AVF5-250</b>   | <b>\$711.25</b> |



AV5-250NYFD

AVF5-250

